


**ENVIRONMENTAL INVESTIGATION
SOUTH BEND LATHE
400 W. SAMPLE STREET
SOUTH BEND, INDIANA**


JULY 31, 1992

**PREPARED FOR
TURNMASTER CORPORATION**

**PREPARED BY
EIS ENVIRONMENTAL ENGINEERS, INC.
1701 NORTH IRONWOOD DRIVE
SOUTH BEND, INDIANA**



John B. Wingard, P.E.
Senior Engineer



H. Stephen Nye, P.E.
President

1.0 INTRODUCTION

EIS Environmental Engineers, Inc. (EIS) of South Bend, Indiana was retained by the Turnmaster Corporation of Carson, California to conduct an environmental investigation of the South Bend Lathe property located at 400 W. Sample Street in South Bend, Indiana. The site location is indicated on Figure 1.1.

1.1 Purpose

The purpose of the investigation was to determine if soil or groundwater contamination was present near five underground storage tanks (USTs) and an associated fuel oil piping track, to collect and analyze samples of possible asbestos-containing roofing materials, and to develop rough cost estimates of possible tank removal and asbestos abatement costs.

1.2 Scope


The scope of the investigation included conducting eight soil borings at selected locations adjacent to the USTs and fuel oil piping track. Soil and groundwater samples were collected from each borehole for laboratory analysis. Soil samples were screened for Volatile Organic Compounds (VOC) with a field Photoionization Detector (PID) analyzer, and selected samples were analyzed for Total Petroleum Hydrocarbons (TPH) by the EIS laboratory. Groundwater samples collected from two borings adjacent to a waste oil tank were analyzed for TPH and VOC. The remaining groundwater samples were analyzed for Benzene, Toluene, Ethyl Benzene and Xylenes (BTEX). A total of 24 samples of possible asbestos-containing roofing materials were also collected for laboratory asbestos analysis.



Approximate Scale 1 in - 2000
 USGS 7.5 Minute Series
 SOUTH BEND EAST, SOUTH BEND WE

SITE LOCATION

FIGURE 1.1
SITE LOCATION MAP
 SOUTH BEND LATHE
 400 W. SAMPLE STREET
 SOUTH BEND, INDIANA



0 40'

SCALE

FIGURE 2.1
 SOUTHWEST SITE PLAN
 SOUTH BEND LATHE
 400 W. SAMPLE ST.
 SOUTH BEND, INDIANA


KEY
 ● SOIL BORING LOCATION



0 40'



SCALE



KEY
● SOIL BORING LOCATION

FIGURE 2.2
SOUTHEAST SITE PLAN
SOUTH BEND LATHE
400 W. SAMPLE ST.
SOUTH BEND, INDIANA

**TABLE 3.1
TPH AND BTEX
ANALYTICAL RESULTS
SOIL & GROUNDWATER SAMPLES**

<u>Sample</u>	<u>Units</u>	<u>TPH</u>	<u>Benzene</u>	<u>Ethyl- Benzene</u>	<u>Toluene</u>	<u>Xylenes</u>
B-1(1.5-3.0)	ppm	4,530*	-	-	-	-
B-1(GW)	mg/l	15*	<0.001	<0.001	<0.001	<0.001
B-2(16.5-18)	ppm	10,400*	-	-	-	-
B-2(GW)	mg/l	124*	<0.001	<0.001	<0.001	0.013
B-3(19.5-21)	ppm	<10	-	-	-	-
B-3(GW)	mg/l	-	<0.001	<0.001	<0.001	<0.001
B-4(19.5-21)	ppm	<10	-	-	-	-
B-4(GW)	mg/l	-	<0.001	<0.001	<0.001	<0.001
B-5(1.5-3.0)	ppm	2,550	-	-	-	-
B-5(16.5-18)	ppm	112	-	-	-	-
B-5(GW)	mg/l	0.44	<0.001	<0.001	0.010	0.008
B-6(1.5-3.0)	ppm	<10	-	-	-	-
B-6(GW)	mg/l	-	<0.001	<0.001	<0.001	<0.001
B-7(10.5-12)	ppm	<10	-	-	-	-
B-7(GW)	mg/l	-	<0.001	<0.001	<0.001	<0.001
B-8(1.5-3.0)	ppm	<10	-	-	-	-
B-8(GW)	mg/l	0.59	<0.001	<0.001	<0.001	<0.001

* By IR Method (418.1).

TABLE 3.2
NON-BTEX VOC DETECTED IN
GROUNDWATER SAMPLES

<u>Parameter</u>	<u>Results</u>					<u>EPA</u> <u>ug</u>
	<u>B-1(GW)</u> <u>ug/l</u>	<u>B-2(GW)</u> <u>ug/l</u>	<u>B-3(GW)</u> <u>ug/l</u>	<u>B-4(GW)</u> <u>ug/l</u>	<u>B-5(GW)</u> <u>ug/l</u>	
1,1-Dichloroethane	2.9	--	2.0	1.7	1.5	--
c-1,2-Dichloroethene	--	--	4.6	3.6	3.5	70
1,1,1-Trichloroethane	--	--	3.1	2.4	1.4	200
Trichloroethene	--	--	15	10	11	5
p-Isopropyltoluene	--	24	--	--	--	--
Naphthalene	--	20	--	--	--	--
1,2,4-Trimethylbenzene	--	125	--	--	--	--
1,3,5-Trimethylbenzene	--	40	--	--	--	--
Xylenes	--	125	--	--	--	--

* Maximum Contaminant Level (MCL) specified in EPA National Primary Drinking Water Standards.

The groundwater samples from borings B-3, B-4, and B-5 were found to contain levels of Trichloroethene (TCE) which were two to three times the Maximum Contaminant Level (MCL) for this compound specified in the EPA Drinking Water Standards. All relatively high levels of TPH were detected in the groundwater samples from borings B-1 and B-2. In our opinion, the levels of contamination found in the groundwater samples suggest that additional investigation should be conducted and that corrective action may be required.

3.3 Asbestos Analytical Results

The analytical results are summarized in Table 3.3. The laboratory analytical reports are included in Appendix A.

The results of the survey of suspect asbestos-containing materials (ACM) are summarized in Table 3.4.

3.4 Rough Cost Estimate

The rough cost estimates based on contractor information for possible asbestos abatement costs and possible removal costs for the waste oil and gasoline USTs are provided in Tables 3.5 and 3.6.

TABLE 3.6
ROUGH COST ESTIMATES - TANK REMOVAL

- Removal of 6,000-gallon waste oil tank and up to 200 C.Y. of non-hazardous petroleum hydrocarbon-contaminated soil, including compacted backfill, concrete repair, clearance sampling/analysis, landfilling of contaminated soil.

\$20,000 to \$30,000

- Removal of 5,000-gallon gasoline tank and up to 25 C.Y. of non-hazardous contaminated soil, including compacted backfill, concrete & fence repair, clearance sampling/analysis, soil disposal.

\$9,000 to \$13,000